

Specifications

Application Class	13–16 t excavator / drilling rig / crawler crane
Max Flow	138.6 L/min
Relief Valve Set Pressure	34.3 MPa
Motor Displacement	92.5 cm³ (max. 95.34), speed-2: 50.6 cm³
Gear Ratio	49.569
Theoretical Output Speed	30.2 / 55.2 min⁻¹ (max. 60)
Theoretical Output Torque	25,056 N·m (max. 25,800)

Fits these machines

13–16 t excavators

And more models - contact us for the full fitment list.

Interchange / related numbers

FDT26, FTD26

Supply and commercial terms

Dispatch	Cross-border direct from Guangzhou; no local warehouse.
Shipping	Express / air / sea; export packing on request.
Lead time, packing, freight, payment, warranty	Confirmed per order on the quotation, in writing.
Reply time	Within 12 working hours - EN / ZH / RU / AR / FR / PT.

Before you order

Parts for travel devices are confirmed per order against the factory parts book - there is no published position-numbered parts table for this family, so we do not print one. Send the machine model and the unit nameplate and we confirm the internal parts, seal kit and brake parts before quoting. Fitment lists are compiled from public market data; contact us to confirm your exact machine and shaft / control variant.

Photo: our own unit photo. Structure drawing: FRANK English sample catalogue, page 63.