

Specifications

Application Class	28~34 t excavator / drilling rig / crawler crane
Theoretical Output Torque	max. 70,000 N·m (7,140 kgf·m)
Theoretical Output Speed	max. 50 min ⁻¹
Max Pressure	35.8 MPa (365 kgf/cm ²)
Brake Torque	1,128 N·m (at motor shaft)
Flange Pitch Circles	D1 425 / D4 490 mm
Flange Diameters	D2 380 / D3 450 mm
Axial Lengths	L1 575 / L2 112 / L3 290 / L4 173 mm
Ports	SAE 1" / PF 1/4 / PF 1/2
Bolt Patterns	26-M20 / 24-M20
Cross Reference	NABTESCO GM60VA / DOOSAN TM60VC/VD / KAYABA MAG23...
Application	Kobelco, Sumitomo, JCB, DOOSAN, VOLVO, HYUNDAI, SANY, ...
Line	FTD70 travel drive assembly (swash plate piston motor + two-st...

Fits these machines

28~34 t excavators

And more models - contact us for the full fitment list.

Interchange / related numbers

FTD70, GM60VA

Supply and commercial terms

Dispatch	Cross-border direct from Guangzhou; no local warehouse.
Shipping	Express / air / sea; export packing on request.
Lead time, packing, freight, payment, warranty	Confirmed per order on the quotation, in writing.
Reply time	Within 12 working hours - EN / ZH / RU / AR / FR / PT.

Before you order

Machine classes and cross-references are taken from the manufacturer's travel device comparison table. Confirm the flange, ratio and brake torque on your machine before ordering.

Photo: manufacturer's official travel drive image (range illustration). We photograph the exact unit we ship before dispatch — send us your nameplate.