

Specifications

Displacement	112 mL/r (per pump)
Rated Pressure	34.3 MPa
Peak Pressure	39.2 MPa
Max Speed	2,700 min ⁻¹
Max Self Priming Speed	2,360 min ⁻¹
Max Input Torque	588 N·m
Pto Max Input Torque	125 N·m
Line	K3V112 / K5V140 tandem series
Application Class	20–25 t hydraulic excavator

Fits these machines

SANY SY215, SANY SY225, Volvo EC210B, Volvo EC210D, Doosan DH220-5, Hyundai R220-5, Kato HD820, Komatsu PC200-8

And more models - contact us for the full fitment list.

Interchange / related numbers

K3V112, K3V112DT, K3V112DTP, K3V112DTP1, K3V112DTP2, K3V112DTPH, K3V112S

Supply and commercial terms

Dispatch	Cross-border direct from Guangzhou; no local warehouse.
Shipping	Express / air / sea; export packing on request.
Lead time, packing, freight, payment, warranty	Confirmed per order on the quotation, in writing.
Reply time	Within 12 working hours - EN / ZH / RU / AR / FR / PT.

Before you order

Fitment lists are compiled from public market data; contact us to confirm your exact machine and shaft / control variant.

Cross-border direct dispatch from Guangzhou; no local warehouse. Express / air / sea available.