

Specifications

Displacement	140 mL/r (per pump)
Rated Pressure	34.3 MPa
Peak Pressure	39.2 MPa
Max Speed	2,500 min ⁻¹
Max Self Priming Speed	2,150 min ⁻¹
Max Input Torque	1,120 N·m
Pto Max Input Torque	294 N·m
Line	K3V140 / K3V180 / K5V160 tandem series
Application Class	27–33 t hydraulic excavator

Fits these machines

SANY SY330, Volvo EC300, Volvo EC290B, Doosan DH300-7, Hyundai R300LC-7, Komatsu PC300-7
And more models - contact us for the full fitment list.

Interchange / related numbers

K3V140, K3V140DT, K3V140DTP, K3V140DTPH, K3V140S

Supply and commercial terms

Dispatch	Cross-border direct from Guangzhou; no local warehouse.
Shipping	Express / air / sea; export packing on request.
Lead time, packing, freight, payment, warranty	Confirmed per order on the quotation, in writing.
Reply time	Within 12 working hours - EN / ZH / RU / AR / FR / PT.

Before you order

Fitment lists are compiled from public market data; contact us to confirm your exact machine and shaft / control variant.

Cross-border direct dispatch from Guangzhou; no local warehouse. Express / air / sea available.