

Specifications

Displacement	180 mL/r (per pump)
Rated Pressure	34.3 MPa
Peak Pressure	39.2 MPa
Max Speed	2,300 min ⁻¹
Max Self Priming Speed	1,950 min ⁻¹
Max Input Torque	1,120 N·m
Pto Max Input Torque	294 N·m
Line	K3V140 / K3V180 / K5V160 tandem series
Application Class	36–40 t hydraulic excavator

Fits these machines

SANY SY375, Volvo EC360, Volvo EC380, Doosan DH370, Komatsu PC350, Komatsu PC400, Hyundai R380
And more models - contact us for the full fitment list.

Interchange / related numbers

K3V180, K3V180DT, K3V180DTP, K3V180DTH, K3V180S

Supply and commercial terms

Dispatch	Cross-border direct from Guangzhou; no local warehouse.
Shipping	Express / air / sea; export packing on request.
Lead time, packing, freight, payment, warranty	Confirmed per order on the quotation, in writing.
Reply time	Within 12 working hours - EN / ZH / RU / AR / FR / PT.

Before you order

Fitment lists are compiled from public market data; contact us to confirm your exact machine and shaft / control variant.

Photo pending: awaiting a K3V180DT / K5V160DTH unit photo. Shown unit is from the neighbouring large class for scale reference.