

Specifications

Displacement	140 mL/r (per pump)
Rated Pressure	34.3 MPa
Peak Pressure	39.2 MPa
Max Speed	2,500 min ⁻¹
Max Self Priming Speed	2,160 min ⁻¹
Max Input Torque	843 N·m
Pto Max Input Torque	125 N·m
Line	K3V112 / K5V140 tandem series
Application Class	27–33 t hydraulic excavator

Fits these machines

SANY SY335, SANY SY365, Volvo EC300D, Doosan DH300-9, Komatsu PC300-8, Hyundai R300-9

And more models - contact us for the full fitment list.

Interchange / related numbers

K5V140, K5V140DT, K5V140DTP, K5V140DTP1, K5V140S

Supply and commercial terms

Dispatch	Cross-border direct from Guangzhou; no local warehouse.
Shipping	Express / air / sea; export packing on request.
Lead time, packing, freight, payment, warranty	Confirmed per order on the quotation, in writing.
Reply time	Within 12 working hours - EN / ZH / RU / AR / FR / PT.

Before you order

Fitment lists are compiled from public market data; contact us to confirm your exact machine and shaft / control variant.

Photo shows a K5V160DT from the same K5V140 / K5V160 series - same body and regulator layout, different displacement plate.