

Specifications

Displacement	200 mL/r (per pump)
Rated Pressure	34.3 MPa
Peak Pressure	39.2 MPa
Max Speed	2,200 min ⁻¹
Max Self Priming Speed	1,900 min ⁻¹
Max Input Torque	1,120 N·m
Pto Max Input Torque	294 N·m
Line	K3V180 / K5V200DTH tandem series
Application Class	40–45 t hydraulic excavator

Fits these machines

SANY SY485, Volvo EC460, Volvo EC480, Doosan DH500, Komatsu PC450, Komatsu PC490, Hyundai R450

And more models - contact us for the full fitment list.

Interchange / related numbers

K5V200, K5V200DT, K5V200DTP, K5V200DTH, K5V200SH

Supply and commercial terms

Dispatch	Cross-border direct from Guangzhou; no local warehouse.
Shipping	Express / air / sea; export packing on request.
Lead time, packing, freight, payment, warranty	Confirmed per order on the quotation, in writing.
Reply time	Within 12 working hours - EN / ZH / RU / AR / FR / PT.

Before you order

Fitment lists are compiled from public market data; contact us to confirm your exact machine and shaft / control variant.

Cross-border direct dispatch from Guangzhou; no local warehouse. Express / air / sea available.