

Specifications

Displacement	121.6 / 129 / 129.2 cm ³ (motor variants)
Rated Pressure	34.3 MPa
Peak Pressure	41.2 MPa
Max Speed	1,850 min ⁻¹
Max Input Torque	874 N·m (max. brake torque)
Line	M5X130 swing motor / M5X130-FRG11 / FRG14 swing device
Application Class	12–15 t hydraulic excavator
Swing Assembly	Two-stage planetary swing device with built-in relief valve, oil fil...
Assembly Reduction Ratio	19.636 (FRG11) / 20.04 (FRG14)

Fits these machines

SANY SY135, Volvo EC140B, Doosan DH150, Komatsu PC130-7, Hyundai R140

And more models - contact us for the full fitment list.

Interchange / related numbers

M5X130, M5X130CHB, M5X130CHB-10A, M5X130-FRG11, M5X130-FRG14

Supply and commercial terms

Dispatch	Cross-border direct from Guangzhou; no local warehouse.
Shipping	Express / air / sea; export packing on request.
Lead time, packing, freight, payment, warranty	Confirmed per order on the quotation, in writing.
Reply time	Within 12 working hours - EN / ZH / RU / AR / FR / PT.

Before you order

Fitment lists are compiled from public market data; contact us to confirm your exact machine and shaft / control variant.

Cross-border direct dispatch from Guangzhou; no local warehouse. Express / air / sea available.